



# EVX12170

|  |   |
|--|---|
| Cells Per Unit                             | 6   |
| Voltage Per Unit                           | 12 V  |
| Capacity                                   | 17 Ah @ 20hr-rate to 1.75V per cell @ 25°C (77°F)   |
| Weight                                     | Approx. 5.67 kg. (12.50 lbs.)   |
| Maximum Discharge Current                  | 230A (5 sec)  |
| Internal Resistance Approx.                | Approx. 13.3mΩ  |
| Operating Temperature Range                | Discharge □ -15□~50□ (5°F~122°F)<br>Charge □ -15□~40□ (5°F~104°F)<br>Storage □ -15□~40□ (5°F~104°F) |
| Nominal Operating Temperature Range        | 25°C ± 3°C (77°F ± 5°F)   |
| Float Charging Voltage                     | 13.5 to 13.8 VDC/unit Average at 25°C (77°F)  |
| Recommended Maximum Charging current limit | 5.1A  |
| Equalization and Cycle Service             | 14.4 to 15.0 VDC/unit Average at 25°C (77°F)  |

|                    |  |
|--------------------|--|
| Self Discharge     | It should be more than 75% of the capacity that before storage after stocked for 6 months at ambient temp. 25° |
| Terminal           | B1/B3-L terminal to accept M5 nut & bolt   |
| Container Material | ABS(UL94-HB)   |