



UP-VWA1232P1

Model No	UP-VWA1232P1
Selling Unit	EACH
Description	UP-VWA1232P1 (UP-RWA1232P1) Panasonic Sealed Lead Acid Battery for Standby, UPS
Application	UPS
Chemistry	Sealed Lead
Voltage	12V
Watt Hour	60Wh
Watts Per Cell	32W
Nominal Capacity	5Ah
Termination	F2, Faston 250 spade terminals
Width	49.5mm
Height	92.5mm
Length/Breadth /Depth	149.5mm
Weight	2000g
Outer Quantity	12
Comments	

This battery is specifically designed for standby use, specifically Uninterruptible Power Supply (UPS) use. This model is not recommended for cyclic use.

This model is fitted with 6.35mm (F2 or Faston 250M) terminals.

New model in flame retardant case (UL94V-0).

Replaces UP-RWA1232P1, UP-RW1232P1, HR1224W, HR6-12, SW200.

Master Instruments is proud to be the official major distributor for Panasonic industrial batteries including Panasonic sealed lead acid (VRLA) batteries in Australia on behalf of [Panasonic Storage Battery \(Shenyang\) Co., Ltd. \(PSBS\)](#)



UL94 V-0 RATED FLAME RETARDANT CASING/HOUSING
This product's casing/housing is classed UL94 V-0. In simple terms, this means that the casing/housing is considered flame retardant in accordance with the plastics flammability standard.

Data Sheet

