



## UP - VWA1232P2

<b>Model No</b>	UP - VWA1232P2
<b>Selling Unit</b>	EACH
<b>Description</b>	UP - VWA1232P2 (UP - RWA1232P2) Panasonic Sealed Lead Acid Battery for Standby, UPS
<b>Application</b>	UPS
<b>Chemistry</b>	Sealed Lead
<b>Voltage</b>	12V
<b>Watt Hour</b>	60Wh
<b>Watts Per Cell</b>	32W
<b>Nominal Capacity</b>	5Ah
<b>Termination</b>	F2 , Faston 250 positive terminal. 4.75mm F1, Faston 187 negative terminal
<b>Width</b>	49.5mm
<b>Height</b>	92.5mm
<b>Length/Breadth /Depth</b>	149.5mm
<b>Weight</b>	2000g
<b>Outer Quantity</b>	12

<b>Suitable For:</b>	<b>MGE Pulsar</b> Ellipse 1200 (3 Batteries Required)	<b>MGE Pulsar</b> Ellipse 650 (2 Batteries Required)	<b>MGE Pulsar</b> Ellipse Premium 500 (2 Batteries Required)
	<b>MGE Pulsar</b> Ellipse 300 (1 Battery Required)	<b>MGE Pulsar</b> Ellipse 800 (2 Batteries Required)	<b>MGE Pulsar</b> Ellipse Premium 650 (2 Batteries Required)
	<b>MGE Pulsar</b> Ellipse 500 (1 Battery Required)	<b>MGE Pulsar</b> Ellipse Premium 1200 (3 Batteries Required)	<b>MGE Pulsar</b> Ellipse Premium 800 (2 Batteries Required)

**Comments**

This battery is specifically designed for standby use, specifically Uninterruptible Power Supply (UPS) use. This model is not recommended for cyclic use.  
 This model is fitted with 6.35mm (F2 or Faston 250M) positive terminal and 4.75mm (F1 or Faston 187) negative terminal.  
 Replaces UP-RWA1232P2, HR1224WF2F1.

Master Instruments is proud to be the official major distributor for Panasonic industrial batteries including Panasonic sealed lead acid (VRLA) batteries in Australia on behalf of [Panasonic Storage Battery \(Shenyang\) Co., Ltd. \(PSBS\)](#)



**UL94 V-0 RATED FLAME RETARDANT CASING/HOUSING**

This product's casing/housing is classed UL94 V-0. In simple terms, this means that the casing/housing is considered flame retardant in accordance with the plastics flammability standard.

**Data Sheet**

