



EVX series EVX 12170



Valve Regulated Lead Acid Battery

Maintenance-Free Sealed Lead Acid Battery.

Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99%.

Design for Cyclic Applications

【Design Life】

400 cycles @ 100%DOD at 25°C

1800 cycles @ 30%DOD at 25°C

【Operating Temperature Range】

Nominal Operating Temperature : 25°C (77°F)

Discharge : -15°C ~ 50°C (5°F~122°F)

Charge: -15°C ~ 40°C (5°F~104°F)

Storage: -15°C ~ 40°C (5°F~104°F)

【Equalization Charging Voltage】

14.4 ~ 15.0 VDC/Unit at 25°C (77°F)


【Self Discharge】

Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F);

Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).

Specification

Nominal Voltage	12V (6 cells per unit)		
Nominal Capacity	17 AH @20HR-rate to 1.75V per cell @25°C (77°F)		
Weight	Approx. 5.67 Kg (12.50 lbs)		
Maximum Discharge Current	230A (5sec)		
Internal Resistance	Approx. 13.3 mΩ		
Short Circuit Current	--		
Maximum Charge Current	5.10A		
Terminal types	B1/B1B/B3 terminal		
Terminal tightening torque	30.4±6.1 Kgf·cm / 26.4±5.3 Lbf·in / 3.0±0.6 N·m		
Container Material	ABS (UL 94-HB)		
Dimensions	Length (L)	181.0±2.0 mm	7.13±0.08 inch
	Width (W)	76.2±1.0 mm	3.00±0.04 inch
	Container Height (h)	167.0±2.0 mm	6.57±0.08 inch
	Overall Height (H)	167.0±2.0 mm	6.57±0.08 inch



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

F.V/Time	30MIN	45MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
1.60V	17.0	12.7	10.3	7.34	5.94	4.43	3.55	2.92	2.51	1.98	1.63	0.93
1.67V	16.5	12.3	9.94	7.14	5.77	4.28	3.43	2.84	2.44	1.92	1.58	0.90
1.70V	16.0	11.9	9.67	6.91	5.62	4.16	3.34	2.76	2.37	1.87	1.54	0.88
1.75V	15.5	11.6	9.38	6.70	5.43	4.04	3.24	2.68	2.30	1.81	1.49	0.85
1.80V	15.0	11.2	9.08	6.48	5.25	3.91	3.14	2.59	2.22	1.75	1.44	0.83
1.85V	14.5	10.8	8.79	6.27	5.09	3.79	3.04	2.51	2.15	1.69	1.39	0.80

Constant Power Discharge Characteristics Unit: W (25°C, 77°F)

F.V/Time	30MIN	45MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
1.60V	204	152	123	88.1	71.6	53.1	42.6	35.0	30.1	23.8	19.6	10.8
1.67V	198	148	120	85.5	69.5	51.3	41.3	34.1	29.3	23.1	18.8	10.4
1.70V	192	143	116	82.9	67.9	49.9	40.1	33.1	28.4	22.4	18.5	10.2
1.75V	186	139	113	80.4	65.5	48.4	38.9	32.1	27.6	21.7	17.9	9.90
1.80V	180	134	109	77.8	63.3	46.9	37.7	31.1	26.7	21.0	17.3	9.59
1.85V	174	130	106	75.3	61.4	45.4	36.5	30.1	25.8	20.3	16.7	9.29

Please refer to the official site for the latest rating confirmation. URL: www.csb-battery.com

Issued: 200120

Sales Offices

日立化成能源科技股份有限公司
Hitachi Chemical Energy Technology Co., Ltd.

BUSINESS HEADQUARTERS

Tel: +886-2-2880-5600

Fax: +886-2-2888-3300

USA OFFICE

Tel: +1-817-244-7777 / 1-(800)3-CSB-USA (272872)

Fax: +1-817-244-4445

SHENZHEN OFFICE (CHINA)

Tel: +86-755-8831-6488, 8831-6775

Fax: +86-755-8831-6075

EUROPE (EMEA) OFFICE

Tel: +31(0)180-418-140

Fax: +31(0)180-418-327

SHANGHAI OFFICE (CHINA)

Tel: +86-21-5046-1622, 5046-0833

Fax: +86-21-5046-1046

TAIPEI OFFICE

Tel: +886-2-2880-5600

Fax: +866-2-2888-3300

BEIJING OFFICE (CHINA)

Tel: +86-10-5820-5336, 5820-5338

Fax: +86-10-5820-3053



MH14533

Recognized under UL 1989,
and certified by ISO 9001, 14001.